



Belle Skirt Clamp



INDUSTRIES SERVED

Coal (Surface/Underground)

Hard Rock (Gold, Copper,
Platinum, Iron Ore, etc)

Ports

Load Out Facilities

Salt

Steel

Chemical

Fertilizer

Sugar

Sand & Gravel

Aggregate

Crushed Stone

Mobile Crushing

Preparation Plants

Cement

Grain

BENEFITS

- Ensures a consistent seal
- No grooving or top cover belt damage
- Uses skirt rubber 150 mm wide and from 8 – 19 mm thick
- Heavy duty components

FEATURES

- Quick adjustment
- All maintenance can be done from side of conveyor
- Bar can be tack welded in place, making the unit one piece
- No hassle installation
- 1.2 m segments can be combined for a skirting system of any length

ORDERING INFORMATION

Item Code	Ordering Number	Description	Wgt (kgs)
310001	BBSC-2000	2mtr Skirt Assembly	17
310002	BBSC-TP	Toggle Pin	1
310003	BBSC-CP	Clamp Plate	1
310004	BBSC-2000CB	2 mtr Clamp Bar	5
310005	BBSC2000-MC	2 mtr Mounting Channel	3

Each Assembly consists of 1 x Mounting Channel, 1 x Clamp Bar, and 4 x Clamp Plates and Toggle Pins.

CONTACT US

Mail: PO Box 403 Ingleburn NSW 1890
Address: 7 Phiney Place Ingleburn NSW 2565

Phone: + 61 2 9618 9400
Email: info@bbcp.com.au



www.bbcp.com.au
www.facebook.com/BBConveyorProducts